

WAAS  
CH **93643**  
**W29A**

APP CRS  
**296°**

Rwy Idg **7250**  
TDZE **480**  
Apt Elev **501**

**RNAV (GPS) Y RWY 29**  
LOUISVILLE MUHAMMAD ALI INTL (SDF)

▼

▲

Rwy 29 helicopter visibility reduction below RVR 4000 NA. Circling Rwy 11 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -13°C or above 54°C. For inop ALS, increase LPV all Cts visibility to RVR 4500 and LNAV Cts A/B visibility to RVR 5500.

MALSR

MISSED APPROACH: Climb to 4000 direct ZUSAB and on track 269° to DAMEN and hold.

|                          |                                            |                                        |                               |                                |       |
|--------------------------|--------------------------------------------|----------------------------------------|-------------------------------|--------------------------------|-------|
| D-ATIS<br><b>118.725</b> | LOUISVILLE APP CON<br><b>132.075 327.0</b> | LOUISVILLE TOWER<br><b>124.2 257.8</b> | GND CON<br><b>121.7 348.6</b> | CLNC DEL<br><b>126.1 275.8</b> | CPDLC |
|--------------------------|--------------------------------------------|----------------------------------------|-------------------------------|--------------------------------|-------|

MISSED APCH FIX

Procedure NA for arrivals at FINCH on V512 eastbound.

Procedure NA for arrivals at MIXKO on V51 southbound.

ELEV 501

**D**

TDZE 480

4000 ZUSAB tr 269° DAMEN

CUCAK TRUBS

4 NM Holding Pattern

GP 3.00° TCH 59

|                   |                       |                       |                         |                       |
|-------------------|-----------------------|-----------------------|-------------------------|-----------------------|
| CATEGORY          | A                     | B                     | C                       | D                     |
| LPV DA            |                       | 761/40                | 281 (300-¾)             |                       |
| LNAV/VNAV DA      |                       | 920/40                | 440 (500-¾)             |                       |
| LNAV MDA          |                       | 920/40                | 440 (500-¾)             |                       |
| <b>C</b> CIRCLING | 1040-1<br>539 (600-1) | 1140-1<br>639 (700-1) | 1160-1¾<br>659 (700-1¾) | 1400-3<br>899 (900-3) |

LOUISVILLE, KENTUCKY

LOUISVILLE MUHAMMAD ALI INTL (SDF)

Amdt 1A 31OCT24

38°10'N-85°44'W

**RNAV (GPS) Y RWY 29**