


WAAS CH 97506 W15A	APP CRS 147°	Rwy Idg TDZE Apt Elev	8502 215 219
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 15

MOBILE RGNL (MOB)

RNP APCH - GPS.		MALSR		MISSED APPROACH: Climb to 2000 direct JOTEN and on track 189° to SAINT and hold.	
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -4°C or above 42°C. For inop ALS, increase LNAV Cats C/D visibility to RVR 6000. *RVR 1800 authorized with use of FD or AP or HUD to DA.					
ATIS	MOBILE APP CON ★	MOBILE TOWER ★	GND CON	CLNC DEL	UNICOM
124.75 257.85	118.5 269.3	118.3 (CTAF) 239.0	121.9 348.6	119.85	122.95



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 50).					2000	JOTEN	tr 189°	SAINT
4 NM Holding Pattern BAYAS								
6000 ← 327° 2000 ← 147°					1800	1020		
GP 3.00° TCH 55								
6.7 NM					2.4 NM	1.3 NM	1.1 NM	
CATEGORY	A	B	C	D				
LPV DA*	415/24				200 (200-½)			
LNAV/VNAV DA	636/45				421 (500-¾)			
LNAV MDA	620/40				405 (500-¾)			
CIRCLING	680-1	461 (500-1)	740-1½ 521 (600-1½)	780-2 561 (600-2)				

