

WAAS CH 57935 W13A	APP CRS 132°	Rwy Ldg TDZE Apt Elev	4797 811 827
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 13


ROSECRANS MEML (STJ)

ASR/PAR

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C (-4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Straight-In minimums NA at night. Baro-VNAV and VDP NA when using Kansas City Intl altimeter setting. Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Kansas City Intl altimeter setting and increase all DA 97 feet, and LPV visibility ¾ mile all Cats, LNAV/VNAV visibility ¼ mile all Cats; increase all MDA 100 feet and Circling Cat C ½ mile, Cat D ¼ mile.

MISSED APPROACH:
Climb to 3100 direct ZOXAD and hold.

ATIS 125.05	ST. JOSEPH APP CON ★ 120.35 360.8	ST. JOSEPH TOWER ★ 126.9 (CTAF) 239.0	GND CON 121.9	UNICOM 122.95
-----------------------	---	---	-------------------------	-------------------------



4 NM Holding Pattern		OVEGE		UNZAS		3100 ↑		ZOXAD ✦	
3100 ← 312° 132° →		132°		2700		* 2.3 NM to RW13		* LNAV only.	
GP 3.00° TCH 50		2700		RW13					
		6 NM		3.5 NM		2.3 NM			
CATEGORY	A	B	C	D					
LPV DA	1377-1 566 (600-1 1/2)								
LNAV/ VNAV DA	1416-2 1/4 605 (600-2 1/4)								
LNAV MDA	1580-1 769 (800-1)	1580-1 1/4 769 (800-1 1/4)	1580-2 1/2 769 (800-2 1/2)						
CIRCLING	1580-1 753 (800-1)	1580-1 1/4 753 (800-1 1/4)	1620-2 1/2 793 (800-2 1/2)	1640-2 3/4 813 (900-2 3/4)					
MIRL Rwy 13-31 HIRL Rwy 17-35 REIL Rws 17 and 35									