

LOC/DME I-SNA

111.75

Chan 54(Y)

APP CRS

016°

Rwy Ldg

5700

TDZE

56

Apt Elev

56

LOC BC RWY 2L

JOHN WAYNE/ORANGE COUNTY (SNA)

Circling Rwy 20L NA at night.

MISSED APPROACH: Climb to 800 then climbing left turn to 2600 direct SLI VORTAC and hold.

D-ATIS 126.0	SOCAL APP CON 121.3 263.1	JOHN WAYNE TOWER ★ 126.8 (CTAF) 343.625	GND CON 120.8	CLNC DEL 118.0	CPDLC	UNICOM 122.95
-----------------	------------------------------	--	------------------	-------------------	-------	------------------

MINOE I-SNA 10.9		VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 75).		800	2600	SLI
NEWPO INT I-SNA 4.5		WUNAD INT I-SNA 1.8		I-SNA DME ANTENNA		
Disregard GS indications.		ZUSED I-SNA 0.5		5700 X 150		
6.4 NM		2.7 NM		1.3 NM		0.7 NM
CATEGORY	A	B	C	D		
S-LOC 2L	560-1	504 (600-1)	560-1 3/8	504 (600-1 3/8)		
CIRCLING	640-1	584 (600-1)	840-2 1/4 784 (800-2 1/4)	1180-3 1124 (1200-3)		
WUNAD FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)						
S-LOC 2L	480-1	424 (500-1)	480-1 1/4	424 (500-1 1/4)		
CIRCLING	640-1	584 (600-1)	840-2 1/4 784 (800-2 1/4)	1180-3 1124 (1200-3)		
FAF to MAP 3.9 NM						
		Knots	60	90	120	150 180
		Min:Sec	3:54	2:36	1:57	1:34 1:18

SANTA ANA, CALIFORNIA

JOHN WAYNE/ORANGE COUNTY (SNA)

Amdt 14A 12JUN25

33°41'N-117°52'W

LOC BC RWY 2L