

WAAS Ch 53699 W22A	APP CRS 220°	Rwy Idg 6602 TDZE 384 Apt Elev 390
--	------------------------	---

RNAV (GPS) RWY 22

TEXARKANA RGNL-WEBB FLD (TXK)

⚠

DME/DME RNP-0.3 NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C (5°F) or above 48°C (118°F). When local altimeter setting not received, use J Lynn Helms Sevier County altimeter setting and increase all DA/MDA 100 feet, increase LPV all Cats visibility ¼ mile, LNAV/VNAV all Cats visibility ½ mile, LNAV and circling Cat C and D visibility ¼ mile. Baro-VNAV and VDP NA when using J Lynn Helms Sevier County altimeter setting. For inoperative MALSRR when using J Lynn Helms Sevier County altimeter setting increase LPV all Cats visibility to 1¼.

⚠

MALSRR

✈

MISSED APPROACH:
Climb to 2000 direct YOBUG and hold.

ATIS 120.2	FORT WORTH CENTER 123.925 269.475	TEXARKANA TOWER ★ 123.875 (CTAF) 0 235.625	GND CON 119.225
----------------------	---	---	---------------------------

ELEV 390

D TDZE 384

2000

↑

YOBUG

* LNAV only.

RW22

1.2

4 NM

7.3 NM

2100

220°

2100

GP 3.00°

TCH 45

CUDPA

WORPA

Procedure Turn NA

CATEGORY	A	B	C	D
LPV DA	634-1½ 250 (300-1½)			
LNAV/VNAV DA	687-1½ 303 (300-1½) 687-¾ 303 (300-¾)			
LNAV MDA	820-1½ 436 (500-1½) 820-¾ 436 (500-¾) 820-1 436 (500-1)			
CIRCLING	820-1 430 (500-1) 900-1 510 (600-1) 1000-1¾ 610 (700-1¾) 1080-2¼ 690 (700-2¼)			

MIRL Rwy 13-31 **0**

HIRL Rwy 4-22 **0**

TEXARKANA, ARKANSAS

Orig-B 02DEC21

33°27'N-93°59'W

TEXARKANA RGNL-WEBB FLD (TXK)

RNAV (GPS) RWY 22