

WAAS CH 72625 W23A	APP CRS 229°	Rwy Idg TDZE 582 Apt Elev 589
--	------------------------	---

RNAV (GPS) RWY 23

TERRE HAUTE RGNL (HUF')



RNP APCH.

ASR

Baro-VNAV and VDP NA when using Paris altimeter setting. Rwy 23 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter setting not received, use Paris altimeter setting and increase all DA 61 feet and all MDA 80 feet, increase LPV and LNAV/VNAV visibility all Cats ½ SM, increase LNAV and Circling Cats C/D visibilities ¼ SM.

MISSED APPROACH:
Climb to 2600 direct POKHY and hold.

ATIS 127.5 269.375	HULMAN APP CON 125.45 339.8	HULMAN TOWER 134.725 322.475	GND CON 121.6 348.6
------------------------------	---------------------------------------	--	-------------------------------



2600 POKHY	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00°/TCH 50).				4 NM Holding Pattern
*LNAV only	CUVOS 1.7 NM to RW23	IMTEW 2400	IPEDY	229°	6000 2400
	1.2 NM to RW23	1160	2400	049°	GP 3.00° TCH 55
	1.2 NM 0.5 NM	3.8 NM	6.5 NM		
CATEGORY	A	B	C	D	
LPV DA	890-7/8 308 (400-7/8)				
LNAV/VNAV DA	874-7/8 292 (300-7/8)				
LNAV MDA	1000-1	418 (500-1)	1000-1½	418 (500-1½)	
CIRCLING	1040-1	451 (500-1)	1220-1¾ 631 (700-1¾)	1220-2 631 (700-2)	

EC-2, 12 JUN 2025 to 10 JUL 2025

EC-2, 12 JUN 2025 to 10 JUL 2025