



WAAS CH 87000 W11A	APP CRS 113°	Rwy Ldg TDZE 132 Apt Elev 132
--	------------------------	---


RNAV (GPS) Z RWY 11

LAURENCE G HANSCOM FLD (BED)

RNP APCH-GPS. ▼ ▲ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19° C or above 54° C. For inop ALS, increase all LNAV/VNAV Cats visibility to RVR 5500.			MALS R 	MISSED APPROACH: Climb to 1000 then climbing left turn to 2000 direct ZIMOT and hold.		
ATIS 124.6	BOSTON APP CON 124.4 279.6	HANSCOM TOWER ★ 118.5 (CTAF) 0 257.2	GND CON 121.7	CLNC DEL 121.85	UNICOM 122.95	



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 67').				1000 ↑	2000 ↷	ZIMOT ✧
4 NM Holding Pattern						
ZELKA				JOPVU		
6000 ← 293° 1900 → 113°				SUVVO 2.2 NM to RW11		
GP 3.00° TCH 50				1.5 NM to RW11		
1800				880		
6.2 NM				2.9 NM		
0.7				1.5 NM		
CATEGORY	A	B	C	D		
LPV DA	384/24		252 (300-½)			
LNAV/ VNAV DA	474/30		342 (400-¾)			
LNAV MDA	660/24	528 (600-½)	660/55	528 (600-1)		
CIRCLING	720-1	588 (600-1)	880-2¼ 748 (800-2¼)	920-2½ 788 (800-2½)		



113°

7011 X 150

5107 X 150

TWR

A5

A5

29