RNAV (GPS) RWY 21
WHEELING OHIO COUNTY (HLG)

WAAS	APP CRS	Rwy Idg	5002
CH 58240	213°	TDZE	1194
W21A		Apt Elev	1194

RNP APCH.

Rwy 21 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, procedure NA below -17°C or above 54°C.

MISSED APPROACH: Climb to 1700 then climbing right turn to 3100 direct AIR VOR/DME and hold.

ASOS	PITTSBURGH APP CON	WHEELING TOWER ★	GND CON	CLNC DEL	UNICOM
127.375	125.275 285.575	118.1 (CTAF) L 257.8	121.75	125.275 (when twr closed)	122.95



ELEV 1194 TDZE 1194



HIRL Rwy 3-21 L
MIRL Rwy 16-34 L
REIL Rwys 21 and 34 L



CATEGORY	A	B	C	D
LPV DA	1444/50 250 (300-1)			
LNAV/VNAV DA	1653-1⅜ 459 (500-1⅜)			
LNAV MDA	1700/55 506 (600-1)		1700-1⅜ 506 (600-1⅜)	
C CIRCLING	1720-1 526 (600-1)	1740-1 546 (600-1)	1920-2 726 (800-2)	1920-2¼ 726 (800-2¼)

NE-4, 12 JUN 2025 to 10 JUL 2025