

|                                                 |                        |                                                             |
|-------------------------------------------------|------------------------|-------------------------------------------------------------|
| LOC/DME I-TYN<br><b>110.9</b><br>Chan <b>46</b> | APP CRS<br><b>036°</b> | Rwy Idg <b>8000</b><br>TDZE <b>40</b><br>Apt Elev <b>42</b> |
|-------------------------------------------------|------------------------|-------------------------------------------------------------|

ILS or LOC RWY 4R  
LAFAYETTE RGNL/PAUL FOURNET FLD (LFT)

DME required for procedure entry and for LOC only.

**▼** Rwy 4R helicopter visibility reduction below  $\frac{3}{4}$  SM NA. VDP NA when using Acadiana Rgnl altimeter setting. When local altimeter setting not received, use Acadiana Rgnl altimeter setting and increase all MDA 29 feet and all MDA 40 feet, increase S-ILS 4R and S-LOC 4R visibility all Cats  $\frac{1}{8}$  SM, Circling visibility Cat C/D  $\frac{1}{4}$  SM.

**MISSED APPROACH:** Climb to 2000 on LFT R-035 to BEDDY INT/LFT 18.9 DME and hold.

|                |                                    |                                           |                  |                    |                  |
|----------------|------------------------------------|-------------------------------------------|------------------|--------------------|------------------|
| ATIS<br>134.05 | LAFAYETTE APP CON ★<br>121.1 363.0 | LAFAYETTE TOWER ★<br>118.5 (CTAF) 0 257.8 | GND CON<br>121.8 | CLNC DEL<br>125.55 | UNICOM<br>122.95 |
|----------------|------------------------------------|-------------------------------------------|------------------|--------------------|------------------|

