



WAAS CH 86829 W21A	APP CRS 210°	Rwy Ldg TDZE Apt Elev	5204 708 708
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 21
CLINTON MUNI (CWI)

⚠ Rwy 21 helicopter visibility reduction below ¾ SM NA. Baro-VNAV NA when using Davenport altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Davenport altimeter setting: increase all DA 47 feet and all MDA 60 feet. Increase LNAV Cat C visibility ¼ mile.	MISSED APPROACH: Climb to 3000 direct WIKES and on track 234° to CVA VORTAC and hold.
---	---

AWOS-3PT 125.525	QUAD CITY APP CON ★ 125.95 257.8	CLNC DEL 118.5 0	CTAF 122.8
----------------------------	--	----------------------------	----------------------



3000	WIKES	tr 234°	CVA	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00°/TCH 34).	
*LNAV only		OYUYA 2 NM to RW21	XOLDY	CUDMA	4 NM Holding Pattern
RW21		1380*	2400	2400	GP 3.00° TCH 40
2 NM		3.2 NM	6.1 NM		
CATEGORY	A	B	C	D	
LPV DA	958-1		250 (300-1)	NA	
LNAV/VNAV DA	958-1		250 (300-1)	NA	
LNAV MDA	1100-1	392 (400-1)	1100-1 ¾ 392 (400-1 ¾)	NA	
CIRCLING	1140-1 432 (500-1)	1240-1 532 (600-1)	1240-1 ½ 532 (600-1 ½)	NA	

NC-3, 12 JUN 2025 to 10 JUL 2025

NC-3, 12 JUN 2025 to 10 JUL 2025