

WAAS CH 61015 W06A	APP CRS 063°	Rwy Idg TDZE 1107 Apt Elev 1156
--	------------------------	---

RNAV (GPS) RWY 6

FORT DODGE RGNL (FOD)

RNP APCH.

▼

▲

Baro-VNAV NA when using Webster City altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. VDP NA when using Webster City altimeter setting. When local altimeter setting not received, use Webster City altimeter setting: increase LPV DA to 1349 feet; increase LNAV/VNAV DA to 1567 feet and all Cats visibility ¼ SM; increase all MDAs 60 feet and LNAV Cats C/D and Circling Cat C visibility ¼ SM. For inoperative MALSR when using Webster City altimeter setting, increase LPV all Cats visibility to 1 mile.

MALSR

AS

|||||

MISSED APPROACH:
Climb to 3000 direct
OXDAH and hold.

AWOS-3PT 118.775	MINNEAPOLIS CENTER 134.0 288.3	UNICOM 123.0 (CTAF) 📶
----------------------------	--	--

Enroute chart showing flight paths, altitudes, and distances for RNP APCH to RWY 6. Key features include:

- 30 NM to OGGHU (153°/243°) with 3400 ft altitude.
- OGGHU (IAF) 3000 NoPT (5) 153°/243°.
- IF/IAF GEGQI 063°/243° (6) 3000 NoPT (5).
- 4 NM distance to GEGQI (3000 ft).
- 2800 ft altitude at GEGQI.
- FAF EYROV 1343 063°/243° (6) 3000 NoPT (5).
- 1114± ft altitude at EYROV.
- 1764 ft altitude at RW06.
- 30 NM to IQFEF (333°/243°) with 3000 ft altitude.
- IQFEF (IAF) 333°/243°.
- MISSED APCH FIX 4 NM from OXDAH (063°/243°).

ELEV 1156 **D** TDZE 1107

3000 OXDAH

↑

📶

4 NM Holding Pattern

GEGQI

EYROV

RW06

GP 3.00° TCH 54

6 NM 4 NM 1.2 NM

*1.2 NM to RW06 *LNAV only.

CATEGORY	A	B	C	D
LPV DA	1307-½		200 (200-½)	
LNAV/VNAV DA	1525-1		418 (400-1)	
LNAV MDA	1500-½ 393 (400-½)		1500-1 393 (400-1)	
CIRCLING	1560-1 404 (500-1)	1620-1 464 (500-1)	1740-1½ 584 (600-1½)	2080-3 924 (1000-3)

MIRL Rwy 12-30 **📶**

HIRL Rwy 6-24 **📶**

REIL Rwy 12, 24 and 30 **📶**

063° to RW06

1254

6547 X 150 0.3% UP

3301 X 100 0.6% UP

FORT DODGE, IOWA

Amdt 1B 20MAY21

42°33'N-94°12'W

FORT DODGE RGNL (FOD)

RNAV (GPS) RWY 6