

WAAS CH 62820 W05A	APP CRS 049°	Rwy Idg TDZE Apt Elev	5000 48 53
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) RWY 5

SALISBURY-OCEAN CITY WICOMICO RGNL (SBY)

RNP APCH.

▼ Baro-VNAV NA when using Georgetown altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 49°C. Visibility reduction by helicopters NA. When local altimeter setting not received use Georgetown altimeter setting: increase LPV DA to 394 feet and increase all Cats visibility ¼ SM; increase LNAV/VNAV DA to 512 feet and all Cats visibility ¼ SM; increase all MDA 60 feet and LNAV Cat C/D and Circling Cat D visibility ¼ SM.

MISSED APPROACH: Climb to 2000 direct OKKOE and hold.

ASOS
118.325

PATUXENT APP CON ★
127.95 314.0

SALISBURY TOWER ★
119.425 (CTAF) **0**

GND CON
123.775

CLNC DEL
123.775

CLNC DEL
132.45
(when twr closed)

UNICOM
122.95

4 NM Holding Pattern FEYKO		*LNAV only. 2000 OKKOE		
2000 ← 229° GP 3.00° TCH 39		2000 EDITH 2000 ZAGID 2.5 NM to RW05 *880 RW05		
8.1 NM		3.4 NM		
2.5 NM				
CATEGORY	A	B	C	D
LPV DA	342-1		294 (300-1)	
LNAV/VNAV DA	460-1½		412 (500-1½)	
LNAV MDA	440-1		392 (400-1)	
CIRCLING	480-1 427 (500-1)	520-1 467 (500-1)	560-1½ 507 (600-1½)	700-2 647 (700-2)

SALISBURY, MARYLAND
Amdt 1A 25MAR21

SALISBURY-OCEAN CITY WICOMICO RGNL (SBY)
38°20'N-75°31'W

RNAV (GPS) RWY 5