

RNAV (RNP) Z RWY 19L
WICHITA DWIGHT D EISENHOWER NTL (ICT)

T For uncompensated Baro-VNAV systems, procedure NA below -15°C (5°F) or above 54°C (130°F). For inoperative MALSR, increase RNP 0.11 all Cats visibility to ¾ mile and RNP 0.30 all Cats visibility to 1½ mile. GPS required. Simultaneous approach authorized with ILS or LOC RWY 19R. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MISSED APPROACH: Climb to 3600 on track 196° to YELOO and hold.

CLNC DEL
125.7

Procedure NA for arrivals
on HUT VOR/DME
airway radials 016 CW 144.

Procedure NA for arrivals at
FLOSS on V77 northeast bound.

106°
(7)

(IAF)
FLOSS

 $2549 \wedge 2549$

YELOO

016° 196° 4 NM

1000	1000
------	------

HIRL all Rwy's
REIL Rwy's 14 and 32
TDZ/CL Rwy 1L

3600
↑
tr 196°

YELOO

RW19L

KECHI
3000

JAXSU
3600

196°

3000

5.1 NM

8.1 NM

GP 3.00°
TCH 54

CATEGORY	A	B	C	D
RNP 0.11 DA		1570-1/2	250 (300-1/2)	
RNP 0.30 DA		1800-1 1/8	480 (500-1 1/8)	

AUTHORIZATION REQUIRED

WICHITA, KANSAS
Amdt 1A 24MAY18

WICHITA DWIGHT D EISENHOWER NTL (ICT)
37°39'N-97°26'W RNAV (RNP) Z RWY 19L