

LOC I-FLG
110.5

APP CRS
214°

Rwy Idg
TDZE
Apt Elev
7000
7003
7014

ILS or LOC RWY 21
FLAGSTAFF PULLIAM (FLG)

Autopilot coupled approach NA below 7640 feet. DME required. DME from FLG VOR/DME. Simultaneous reception of I-FLG and FLG DME required. For inop ALS increase S-ILS 21 all Cats visibility to %.

MALS

AS

MISSED APPROACH: Climb to 7500, then climbing left turn to 11000 on heading 130° and FLG R-172 to OATES INT/FLG VOR/DME 16.7 DME and hold, continue climb-in-hold to 11000.

ATIS 125.8	PHOENIX APP CON 126.375 236.775	FLAGSTAFF TOWER ★ 134.55 (CTAF) 239.25	GND CON 121.9	UNICOM 122.95
----------------------	---	--	-------------------------	-------------------------

7500		11000	FLG R-172	OATES	FIMAL FLG 10.2	10200	12300	Remain within 10 NM
* LOC only		* FLG 1.3	HEV MU FLG 4.9	SOL BE FLG 0.9	10200	10200	8500*	GS 3.00° TCH 52
0.4		0.5	3.7 NM	5.3 NM				
CATEGORY	A		B		C		D	
S-ILS 21	7258-½		255 (300-½)					
S-LOC 21	7340-½		337 (400-½)					
CIRCLING	7520-1 506 (600-1)		7560-1 546 (600-1)		8100-3 1086 (1100-3)		8560-3 1546 (1600-3)	

ELEV 7014

D

TDZE 7003

HIRL Rwy 3-21

FLAGSTAFF, ARIZONA

Amtd 1 07DEC17

35°08'N-111°40'W

FLAGSTAFF PULLIAM (FLG)

ILS or LOC RWY 21