

WAAS CH 45931 W19A	APP CRS 188°	Rwy Idg TDZE 1409 Apt Elev 1409
--	------------------------	---

RNAV (GPS) RWY 19

BEECH FACTORY (BEC)

⚠


NA

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Obtain local altimeter setting on CTAF; when not received, use Wichita Dwight D Eisenhower Ntl altimeter setting and increase all DA 36 feet and all MDA 40 feet; increase LPV all Cats and LNAV/VNAV all Cats visibility and LNAV Cat C and D visibility ¼ mile and Circling Cat C and D visibility ¼ mile. Baro-VNAV NA with Wichita Dwight D Eisenhower Ntl altimeter setting. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:

Climb to 3000 direct DENEY and hold.

AWOS-3PT 119.45	WICHITA APP CON 134.8 269.1	BEECH TOWER ★ 126.8 (CTAF) 0 313.6	GND CON 121.7	CLNC DEL 125.0 (When tower closed)	UNICOM 122.95
---------------------------	---------------------------------------	--	-------------------------	---	-------------------------



ELEV 1409

TDZE 1409

188° to RWY 19

61

001 X 1008

TWR 1437

0.5% UP

MIRL Rwy 1-19

REIL Rwy 1 and 19

3000	DENEY	TOBEE	DOLBE	4 NM Holding Pattern
*LNAV only	WIBED 1.5 NM to RWY 19	3000	188°	008°
	1920*	3000	188°	3000
	1.5 NM	3.4 NM	6.2 NM	GP 3.00° TCH 45
CATEGORY	A	B	C	D
LPV DA		1659-¾	250 (300-¾)	
LNAV/VNAV DA		1659-¾	250 (300-¾)	
LNAV MDA		1780-1	371 (400-1)	
CIRCLING	1820-1 411 (500-1)	2120-1 711 (800-1)	2120-2 711 (800-2)	2120-2½ 711 (800-2½)

NC-2, 12 JUN 2025 to 10 JUL 2025

NC-2, 12 JUN 2025 to 10 JUL 2025