

WAAS CH 99711 W31A	APP CRS 313°	Rwy Idg TDZE 1389 Apt Elev 1391
--	------------------------	---

RNAV (GPS) RWY 31

BEMIDJI RGNL (BJI)

RNP APCH.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 46°C. For inop ALS, increase LNAV/VNAV all Cats and LNAV Cats C/D visibility to 1¼ SM.

MALSR

MISSED APPROACH:

Climb to 3200 direct TEGAE and hold.

AWOS-3
119.275

MINNEAPOLIS CENTER
134.75 251.1

UNICOM
122.8 (CTAF) **0**

MISSED APCH FIX

133°

313°

4 NM

ELEV 1391 **D** TDZE 1389

HIRL Rwy 13-31 **0**
MIRL Rwy 7-25 **0**
REIL Rwy 7 and 25 **0**

3200 TEGAE

HIPAV 2.6 NM to RW31

IPEMY 3200

OMIGY 4 NM Holding Pattern

*LNAV only.

*1.1 NM to RW31

313°

133°

6000

3200

GP 3.00°

TCH 45°

CATEGORY	A	B	C	D
LPV DA	1589-½ 200 (200-½)			
LNAV/VNAV DA	1825-1 436 (500-1)			
LNAV MDA	1780-½ 391 (400-½)	1780-⅝ 391 (400-⅝)	1780-1 391 (400-1)	
C CIRCLING	1840-1 449 (500-1)	1860-1 469 (500-1)	1860-1½ 469 (500-1½)	1960-2 569 (600-2)

NC-1, 12 JUN 2025 to 10 JUL 2025

NC-1, 12 JUN 2025 to 10 JUL 2025