

LOC I-HYS 111.5	APP CRS 339°	Rwy Idg TDZE Apt Elev	6501 1994 1999
---------------------------	------------------------	-----------------------------	---

ILS or LOC RWY 34

HAYS RGNL (HYS)



ADF required.

When local altimeter setting not received, use Russell altimeter setting: increase DA to 2263 feet; increase all MDA 80 feet and visibility S-LOC 34 Cat C and Circling Cat C and D ¼ SM. For inoperative MALSR when using Russell altimeter setting, increase S-ILS all Cats visibility to 1.

MALSR

MISSED APPROACH: Climb to 2600 then climbing right turn to 3800 direct NETTE LOM/HYS 4.8 DME and hold.

AWOS-3PT 125.525	KANSAS CITY CENTER 124.4 322.4	UNICOM 122.8 (CTAF)
----------------------------	--	-------------------------------



2600	3800	HY	HY	VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 43).
↑	↷	↷	↷	Remain within 10 NM
HYS VORTAC	HYS	HY	HY	3343
HYS	HYS	HY	HY	339°
HYS	HYS	HY	HY	3400
HYS	HYS	HY	HY	3800
HYS	HYS	HY	HY	GS 3.00°
HYS	HYS	HY	HY	TCH 45
HYS	HYS	HY	HY	4.1 NM
CATEGORY	A	B	C	D
S-ILS 34	2194-½	200 (200-½)		
S-LOC 34	2340-½	346 (400-½)	2340-¾	346 (400-¾)
CIRCLING	2480-1	481 (500-1)	2560-1½	2680-2¼