

WAAS CH 82704 W35A	APP CRS 348°	Rwy Idg 5010 TDZE 951 Apt Elev 951
--	------------------------	---

RNAV (GPS) RWY 35
JACKSON COUNTY (JCA)



RNP APCH-GPS.

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C.
▲ Circling NA for Cat D west of Rwy 17-35. Baro-VNAV and VDP NA when using Winder altimeter setting. Rwy 17 helicopter visibility reduction below $\frac{3}{4}$ SM NA. When local altimeter setting not received, use Winder altimeter setting; increase LPV DA to 1232 feet and visibility all Cats $\frac{1}{2}$ SM; increase LNAV/VNAV DA to 1241 feet and visibility all Cats $\frac{3}{4}$ SM; increase all MDAs 40 feet and LNAV visibility Cats C/D $\frac{1}{2}$ SM.

MISSED APPROACH:
Climb to 3700 direct
CERTA and hold.

AWOS-3PT 118.125	ATLANTA APP CON★ 132.475 291.1	UNICOM 122.975 (CTAF) 0
----------------------------	--	-----------------------------------

MISSED APCH FIX



ELEV 951		TDZE 951
----------	--	----------

