



WAAS CH 90441 W32A	APP CRS 316°	Rwy Idg TDZE Apt Elev	3650 1245 1245
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 32

COUNCIL BLUFFS MUNI (CBF)

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). DME/DME RNP- 0.3 NA.	MISSED APPROACH: Climb to 2000 then climbing right turn to 3900 direct EVHAP and hold.
---	--

AWOS-3 126.575	OMAHA APP CON 124.5 263.0	CLNC DEL 127.675	UNICOM 122.725 (CTAF) ①
--------------------------	-------------------------------------	----------------------------	-----------------------------------



2000	3900	EVHAP	VGSI and RNAV glidepath not coincident (VGSI Angle 3.50/TCH 30).		4 NM Holding Pattern
* LNAV only	CAVPI 1.7 NM to RW32	FEHEV	EVHAP	136°	3900
* 0.9 NM to RW32	1820*	2900	2900	316°	GP 3.00° TCH 40
0.9 0.8 3.4 7 NM					
CATEGORY	A	B	C	D	
LPV DA	1445-¾		200 (200-¾)		
LNAV/VNAV DA	1495-¾		250 (300-¾)		
LNAV MDA	1620-1		375 (400-1)		
☑ CIRCLING	1780-1	535 (600-1)	1780-1½ 535 (600-1½)	1880-2 635 (700-2)	