WEAZL FIVE DEPARTURE (RNAV)

RNAV 1 - DME/DME/IRU or GPS. **TOP ALTITUDE:** 3000 RADAR required.

14300 *6400 -003° (45)

WEAZL ≺

WHFRD

CLAWD ≺

SALISBURY, NORTH CAROLINA

CHARLOTTE DEP CON 128.325 307.8

> AWOS-3 118.175 CLNC DEL 127.35 UNICOM 122.725



NOTE: For turbo jets only.

NOTE: If unable to accept climb rates,

advise ATC on initial contact.

NOTE:

Upon reaching 10000 MSL, accelerate to

and maintain 280K, if unable advise ATC.



TAKEOFF MINIMUMS

Rwy 2: Standard.

Rwy 20: 400-2³/₄ or standard with minimum climb of 205' per NM to 1300, or alternatively, with standard takeoff minimums and a normal 200' per NM climb gradient, takeoff must occur no later than 1200' prior to DER.

NOTE: Chart not to scale.

V

12 JUN 2025

ಠ

10 JUL 2025

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 2: Climb on heading assigned by ATC, thence TAKEOFF RUNWAY 20: Climb on heading 202° to 1700 before turning right, then on heading assigned by ATC, thence

. . . . on RADAR vectors to WHFRD, then on track 003° to WEAZL, then on CLAWD Transition. Maintain 3000, expect clearance to filed altitude within 10 minutes after departure.

CLAWD TRANSITION (WEAZL5.CLAWD)