


▼

▲NA

DME/DME RNP-0.3 NA. Rwy 18 helicopter visibility reduction below 1 SM NA. Straight-in/Circling to Rwy 18 NA at night. Use Greenville altimeter setting, when not received, use Greenwood altimeter setting and increase all MDA 40 feet, increase LNAV Cat C/D visibility 1/8 SM and Circling Cat C/D visibility 1/4 SM.

MISSED APPROACH: Climb to 2500 direct WUPUK and hold.

GLH ASOS 125.525	MEMPHIS CENTER 135.875 269.35	UNICOM 122.8 (CTAF) 0
---------------------	----------------------------------	--------------------------



MISSED APCH FIX WUPUK		ELEV 126		TDZE 126	
4 NM Holding Pattern		JOKAK		WUPUK	
2600		TECUK		WOPKI	
360°		1700		1.6 NM to RW18	
180°		680		RW18	
6.6 NM		3.2 NM		1.6 NM	
CATEGORY	A	B	C	D	
LNAV MDA	520-1	394 (400-1)	520-1 1/8	394 (400-1 1/8)	
CIRCLING	580-1 454 (500-1)	600-1 474 (500-1)	840-2 714 (800-2)	840-2 1/4 714 (800-2 1/4)	
MIRL Rwy 18-36 0					