

WAAS CH 90141 W23A	APP CRS 233°	Rwy Idg 7001 TDZE 671 Apt Elev 683
--	------------------------	---

RNAV (GPS) RWY 23

CHARLOTTE/MONROE EXEC (EQY)


RNP APCH-GPS.




Rwy 23 helicopter visibility reduction below $\frac{3}{4}$ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C or above 54°C .

MISSED APPROACH: Climb to 1200 then climbing left turn to 3000 direct ZOPOC and hold.

ASOS 135.775	CHARLOTTE APP CON 120.05 307.8	CLNC DEL 132.55	UNICOM 122.7 (CTAF) 0
------------------------	--	---------------------------	---------------------------------



ELEV 683	TDZE 671
----------	----------



HIRL Rwy 5-23 **L**
REIL Rwy 23 **L**

MONROE, NORTH CAROLINA
Amdt 1C 30NOV23

35°01'N-80°37'W

CHARLOTTE/MONROE EXEC (EQY)
RNAV (GPS) RWY 23

SE-2, 12 JUN 2025 to 10 JUL 2025

1200 ↑		3000 ↖		ZOPOC △		XEWIR 2.5 NM to RW23 1.2 NM to RW23 ELLYE 2300 JAMSR 3000 233° GP 3.00° TCH 40 1480 2300 1.2 NM 1.3 NM 2.5 NM 6 NM			
CATEGORY		A		B		C		D	
LPV DA				939-1		268 (300-1)			
LNAV/ VNAV DA				981-1		310 (300-1)			
LNAV MDA		1080-1 409 (400-1)				1080-1½ 409 (400-1½)			
C CIRCLING		1220-1 537 (600-1)				1220-1½ 537 (600-1½)		1480-2½ 797 (800-2½)	