


WAAS CH 53326 W12A	APP CRS 129°	Rwy Idg TDZE Apt Elev	4762 800 800
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 12

HASTINGS (9D9)

RNP APCH - GPS.		MISSED APPROACH: Climb to 3000 direct DERRE and hold.
Circling NA to Rwy 9, 18, 27 and 36. Baro-VNAV NA. Use GRR altimeter setting; when not received, use Y70 altimeter setting: increase LPV DA to 1102 feet; increase LNAV/VNAV DA to 1260 feet and all visibilities $\frac{1}{8}$ SM; increase all MDA 20 feet, and LNAV visibility Cat C $\frac{1}{8}$ SM. Rwy 12 helicopter visibility reduction below $\frac{3}{4}$ SM NA.		

GRR ASOS 118.725	GREAT LAKES APP CON * 128.4 257.6	UNICOM 123.075 (CTAF) 0
----------------------------	---	-----------------------------------



4 NM Holding Pattern		VGSI and RNAV glidepath not coincident (VGSI Angle 4.00/TCH 34).		3000	DERRE
BLBBY		AGEYU		RW12	
3000		2300		1440	
GP 3.00° TCH 40		EDGE 1.9 NM to RW12		RW12	
5.8 NM		2.7 NM		1.9 NM	
CATEGORY	A	B	C	D	
LPV DA	1087-1	287 (300-1)		NA	
LNAV/VNAV DA	1245-1 $\frac{3}{8}$	445 (500-1 $\frac{3}{8}$)		NA	
LNAV MDA	1240-1	440 (500-1)	1240-1 $\frac{1}{4}$ 440 (500-1 $\frac{1}{4}$)	NA	
CIRCLING	1380-1 580 (600-1)	1440-1 640 (700-1)	1440-1 $\frac{3}{4}$ 640 (700-1 $\frac{3}{4}$)	NA	

MIRL Rwy 12-30 0
REIL Rwy 12 and 30 0