

WAAS CH 99306 W32A	APP CRS 316°	Rwy Idg 6021 TDZE 323 Apt Elev 327
--	------------------------	---

RNAV (GPS) RWY 32

EAST GEORGIA RGNL (SBO)

T Baro-VNAV and VDP NA when using Vidalia altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C (5°F) or above 54°C (130°F).

A When local altimeter setting not received, use Vidalia altimeter setting and increase all DA to 638 feet and all MDA 80 feet; increase LNAV Cats C/D visibility ½ SM, and Circling Cats C/D visibility ¼ SM. DME/DME RNP-0.3 NA. Rwy 32 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 800 then climbing left turn to 2500 direct WINSI and hold.

AWOS-3 133.375	ATLANTA CENTER 127.95 343.75	UNICOM 122.975 (CTAF) ①
--------------------------	--	-----------------------------------




Diagram illustrating the HIRL Rwy 14-32 and its associated instrument approach procedure.

Diagram Details:

- Runway: 6021 x 100, 316° heading, 32° heading.
- Approach: 4 NM Holding Pattern, 136° turn, 316° turn, 2000 ft altitude.
- Obstacles: 800, 2500, WINSI, JIDIK 2000, RW32, 2000.
- Distances: 1.3, 3.8 NM, 6.9 NM.

Procedure Table:

CATEGORY	A	B	C	D
LPV DA	573-1	250 (300-1)		
LNNAV/ VNAV DA	573-1	250 (300-1)		
LNNAV MDA	780-1	457 (500-1)	780-1 $\frac{3}{8}$	457 (500-1 $\frac{3}{8}$)
CIRCLING	900-1 573 (600-1)	920-1 593 (600-1)	1000-2 673 (700-2)	1000-2 $\frac{1}{4}$ 673 (700-2 $\frac{1}{4}$)