


WAAS CH 87036 W34A	APP CRS 335°	Rwy Idg TDZE Apt Elev	4997 83 83
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) RWY 34
DE QUINCY INDUSTRIAL AIRPARK (5R.8)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Helicopter visibility reduction below 3/4 SM NA. When local altimeter setting not received, use Sulphur altimeter setting and increase all DA 55 feet and MDA 60 feet, increase LPV and LNAV/VNAV visibility all Cats 1/4, LNAV and Circling Cat C visibility 3/8 mile. Baro-VNAV and VDP NA with Sulphur altimeter setting. Night landing Rwy 16 NA.

MISSED APPROACH: Climb to 1700 direct FEPRO and hold.

AWOS-3PT 121.2	LAKE CHARLES APP CON ★ 119.35 282.3	UNICOM 122.8 (CTAF) ①
--------------------------	---	---------------------------------



1700 FEPRO CIXET 2 NM to RW34 QUNKE 1700 HATGU 1700 GP 3.00° TCH 50			
*LNAV only			
CATEGORY	A		D
LPV DA	339-3/4		NA
LNAV/VNAV DA	333-3/4		NA
LNAV MDA	540-1	457 (500-1)	NA
CIRCLING	540-1	740-1	NA
	457 (500-1)	657 (700-1)	NA

SC-4, 12 JUN 2025 to 10 JUL 2025

SC-4, 12 JUN 2025 to 10 JUL 2025