

WAAS CH 99644 W18A	APP CRS 180°	Rwy Idg TDZE Apt Elev	6001 1316 1316
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 18

MONETT RGNL (HFJ)

RNP APCH - GPS.

▼

⚠

Baro-VNAV and VDP NA when using Joplin altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Joplin altimeter setting; increase LPV DA to 1678 feet and all visibilities ¼ SM; increase LNAV/VNAV DA to 1742 feet and all visibilities ⅓ SM; increase all MDAs 120 feet and LNAV visibility Cat C/D ½ SM, and Circling visibility Cat C/D ½ SM.

MISSED APPROACH: Climb to 3100 direct STERL and hold.

AWOS-3 118.275	SPRINGFIELD APP CON 124.95 318.2	CLNC DEL 121.85	UNICOM 123.075 (CTAF) 📻
--------------------------	--	---------------------------	--

ELEV 1316 TDZE 1316

180°

81

6001 X 100

0.3% UP

36

HIRL Rwy 18-36 **📻**

REIL Rwy 18 **📻**

3100	STERL	SOFWR	PHENM	4 NM Holding Pattern
KNOXX 1.9 NM to RW18	1.1 NM to RW18	0.8	3.3 NM	6 NM
1960	180°	3000	360°	4000 3000
GP 3.00°	TCH 43			
CATEGORY	A	B	C	D
LPV DA	1566-¾	250 (300-¾)		
LNAV/VNAV DA	1630-⅞	314 (400-⅞)		
LNAV MDA	1700-1	384 (400-1)	1700-1½	384 (400-1½)
CIRCLING	1760-1 444 (500-1)	1900-1 584 (600-1)	1900-1½ 584 (600-1½)	2060-2½ 744 (800-2½)

MONETT, MISSOURI
Orig 03NOV22

36°54'N-94°01'W

MONETT RGNL (HFJ)

RNAV (GPS) RWY 18

NC-3, 12 JUN 2025 to 10 JUL 2025

NC-3, 12 JUN 2025 to 10 JUL 2025