

WAAS
CH **61328**
W13A

APP CRS
134°

Rwy Idg
TDZE
Apt Elev

4001
616
616

RNAV (GPS) RWY 13
TRI-TOWNSHIP (SFY)

⚠

When local altimeter setting not received, use Sterling/Rockfalls altimeter setting and increase all MDA 80 feet. Procedure NA at night. DME/DME RNP-0.3 NA. Helicopter visibility reduction below 1 SM NA.

MISSED APPROACH:

Climb to 1020 then climbing right turn to 3000 direct CONAT and hold.

AWOS-3PT
118.650

QUAD CITY APP CON★
125.95 257.8

UNICOM
122.7 (CTAF) 0

The chart displays the RNAV (GPS) RWY 13 approach. The final approach segment is a 3.1 NM straight-in from 3000 feet to 2400 feet, then a 2.5 NM segment to 1440 feet, and a 2.5 NM segment to the runway. Key features include:

- Obstacles:** LOTTE (3000, 102°, 116.1), WACKS (3000, 274°, 10.5), ACEMI (1179±), ZITSA (702±), RW13 (689±), RW13 (748±), and a 1106 obstacle.
- Altitudes:** 3000, 2400, 1440, 1020, and 3000.
- Distances:** 4 NM, 3.1 NM, 2.5 NM, and 2.5 NM.
- Angles:** 314°, 134°, 180°, and 089°.
- Navigation:** (IAF) NORPY, (IAF) TROST, (IF/IAF) CONAT, (FAF) ACEMI, and ZITSA.
- MSA:** MSA RW13 25 NM with a 2700 foot minimum safe altitude.

4 NM Holding Pattern

Visual Segment - Obstacles.

1020 3000 CONAT

3000 ← 314°

134° →

134°

2400

ACEMI

ZITSA 2.5 NM to RW13

RW13

1440

5 NM 3 NM 2.5 NM

CATEGORY	A	B	C	D
LP MDA	940-1	324 (400-1)	NA	
LNAV MDA	960-1	344 (400-1)	NA	
CIRCLING	1160-1 544 (600-1)	1220-1 604 (700-1)	NA	

ELEV 616 TDZE 616

134°

314°

4001 X 75

31

MIRL Rwy 13-31 0

SAVANNA, ILLINOIS

Orig-D 30DEC21

42°03'N-90°06'W

TRI-TOWNSHIP (SFY)

RNAV (GPS) RWY 13