

WAAS
CH **50401**
W18A

APP CRS
180°

Rwy Ldg **3500**
TDZE **675**
Apt Elev **675**

RNAV (GPS) RWY 18
LEWIS COUNTY RGNL (6M6)

▼

NA

Baro-VNAV NA. Use Quincy altimeter setting; when not received use Kirksville altimeter setting:
increase LPV DA to 1098 feet; increase LNAV/VNAV DA to 1145 feet; increase all MDA 80 feet.

MISSED APPROACH:

Climb to 2300 direct
GRITE and hold.

UIN ASOS 121.425	KANSAS CITY CENTER 126.225 317.775	UNICOM 122.7 (CTAF) 0
----------------------------	--	---------------------------------

The chart displays the RNAV (GPS) RWY 18 approach. Key features include:

- Waypoints:** WOLER (IAF), VEJTY (IAF), YUKON (FAF), and GRITE.
- Altitudes:** 2500 NoPT (5), 2300 (5.1), 2500, 6000, 2500, 3000, 2700, 796, 857, 1643.
- Distances:** 5 NM, 30 NM to WOLER, 30 NM to GLOBA (NoPT), 30 NM to VEJTY, 4 NM.
- Angles:** 090°, 180°, 270°, 360°.
- Obstacles:** 1643 M.

ELEV **675**

TDZE **675**

81

180°

0.3% UP

3500 X 60

36

MIRL Rwy 18-36 0

2300

GRITE

4 NM

YUKON

2300

GLOBA

4 NM Holding Pattern

360° → 6000

← 180° 2500

GP 3.00°

TCH 40

CATEGORY	A	B	C	D
LPV DA	1035-1¼	360 (400-1¼)	NA	
LNAV/VNAV DA	1082-1½	407 (500-1½)	NA	
LNAV MDA	1220-1	545 (600-1)	NA	

MONTICELLO, MISSOURI

LEWIS COUNTY RGNL (6M6)

Orig-D 05DEC19

40°08'N-91°41'W

RNAV (GPS) RWY 18