

WAAS
CH **42909**
W36A

APP CRS
359°

Rwy Idg
TDZE **54**
Apt Elev **55**

RNAV (GPS) RWY 36

PICAYUNE MUNI (MJD)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C (5°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Stennis Intl altimeter setting. DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA. Procedure NA when R-4403 A, B, C, or E is active. When local altimeter setting not received, use Stennis Intl altimeter setting: increase LPV DA to 338 and all Cats visibility ½ mile; increase LNAV/VNAV DA to 374 and all Cats visibility ½ mile; increase all MDA 40 feet and LNAV Cats C and D visibility ½ mile, and Circling Cat C visibility ¼ mile.

MISSED APPROACH:
Climb to 1800 direct CIQYI and hold.

AWOS-3PT 119.075	GULFPORT APP CON ★ 124.6 354.1	UNICOM 122.8 (CTAF) 0
----------------------------	--	---------------------------------

MISSED APCH FIX

1800	CIQYI				
*LNAV only.					
CATEGORY	A	B	C	D	
LPV DA	304-7/8 250 (300-7/8)				
LNAV/ VNAV DA	340-1 286 (300-1)				
LNAV MDA	420-1 366 (400-1)				
CIRCLING	480-1 425 (500-1)	580-1 525 (600-1)	700-1¾ 645 (700-1¾)	960-3 905 (1000-3)	MRL Rwy 18-36 0

ELEV 55

TDZE 54

PICAYUNE, MISSISSIPPI

Amtd 2 23JUN16

30°29'N-89°39'W

PICAYUNE MUNI (MJD)

RNAV (GPS) RWY 36