10 JUL 2025 to 07 AUG 2025

## KYLOW ONE DEPARTURE (RNAV) (Departure Routes)

RNAV 1- DME/DME/IRU or GPS. From KYLOW on FICKY, GROGU and DINTY Transitions: GPS.

MCKEY, RIZIN, SCTRR and STOKD Transitions: RADAR required for non-GPS equipped aircraft.

## TOP ALTITUDE: FICKY and GROGU TRANSITIONS: 14000: SCTRR, STOKD, MCKEY, DINTY, and

**RIZIN TRANSITIONS: FL230** D-ATIS DEP TAKEOFF MINIMUMS 135.65 Rwy 24L: Standard with minimum climb of 280' per NM to 628. CLNC DEL 120.35 327.0 Rwy 24R: Standard with minimum climb of 260' per NM to 628. **CPDLC** Rwy 25L: Standard with minimum climb of 230' per NM to 628. **GND CON** Rwy 25R: Standard with minimum climb of 260' per NM to 628. (N) 121.65 327.0 (S) 121.75 327.0 (W) 121.4 327.0 LOS ANGELES TOWER (N) 133.9 239.3 (S) 120.95 379.1 SOCAL DEP CON 124.3 363.2 (045°-224°) 125.2 263.025 (225°-044°) **DSTAR** 3000 230K NOTE: Jets only. NOTE: For use only when nighttime noise NSA LAX 25 M abatement procedures are in effect. **EWOKK** NOTE: GROGU Transition ATC assigned 3000 230K only. Do not file. 7800 NOTE: Expect GROGU Transition when W292E is in use. NOTE: File the RIZIN Transition in lieu of the LADYJ DEPARTURE during time periods 2100-0700 LCL. All other times RIZIN Transition ATC assigned only. (CONTINUED ON FOLLOWING PAGE)

## DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 24L/R: Climb on heading 251° to intercept course 190° to cross DSTAR at or below 3000 and at or below 230K, then on track 190° to KYLOW, thence. . . .

TAKEOFF RUNWAYS 25L/R: Climb on heading 251° to intercept course 196° to cross EWOKK at or below 3000 and at or below 230K, then on track 196° to KYLOW, thence. . . .

. . . . (transition). Departures on FICKY and GROGU Transitions maintain 14000. All other Transitions maintain FL230. Expect filed altitude 10 minutes after departure.

KYLOW ONE DEPARTURE (RNAV) (Departure Routes) (KYLOW1.KYLOW) 11JUL24

See following

transition routes

page for

KYLOW

NOTE: Chart not to scale.

LOS ANGELES, CALIFORNIA LOS ANGELES INTL (LAX)