YODUH TWO DEPARTURE (RNAV)

SAN ANTONIO DEP CON 125.1 307.0

RNAV 1 - DME/DME IRU or GPS.

RADAR required for non-GPS equipped aircraft. RADAR required.

TOP ALTITUDE: ASSIGNED BY ATC


NOTE: Aircraft destined for airports north/northeast of DFW terminal area must file the KLNGR Transition.

KLNGR

TAKEOFF MINIMUMS

Rwy 17: Standard with minimum climb of 210'/NM to 2200.

Rwy 35: Standard with minimum climb of 250'/NM to 3800.





SEP 2025

8

2

07 AUG 2025

SC-3,

NOTE: Chart not to scale.

V

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 17: Climb on heading 169° or as assigned by ATC, for vectors to SITHH, thence. . .

TAKEOFF RUNWAY 35: Climb on heading 349° or as assigned by ATC, for vectors to SITHH, thence. . .

. . . on track 002° to YODUH, then on transition. Maintain ATC assigned altitude. Expect filed altitude 10 minutes after departure.

KLNGR TRANSITION (YODUH2.KLNGR)
PRTZY TRANSITION (YODUH2.PRTZY)