

LOC I-DYS 109.9	APCH CRS 344°	Rwy Ldg 13,500 TDZE 1788 Arprt Elev 1790	AL-2 [USAF]
RADAR or DME required.			ALSF-1
* When ALS inop, increase CAT CDE RVR to 40 and vis to ¾ mile. ** When ALS inop, increase CAT CDE vis to 1 ¾ miles.			MISSED APPROACH: Climb to 4000 via DYS TACAN R-349 to BIMET and hold.
ATIS ★ 269.175	ABILENE APP CON 125.0 338.3 EAST 127.2 282.3 WEST	TOWER 133.0 257.675	GND CON 118.35 275.8
			ASR

*** Circling to other than Rwy 16 NA.
 ***** When ALS inop, increase CAT CDE vis to 1 ½ miles.

EMERG SAFE ALT 100 NM 4600

ELEV 1790	TDZE 1788
LIRL Rwy 164°-344° HIRL Rwy 16-34	
FAF to MAP 4.2 NM	
Knots	120 140 160 180 200
Min:Sec	2:06 1:48 1:35 1:24 1:11

CATEGORY	C	D	E
S-ILS 34 *	1988/24	200 (200-½)	
S-LOC 34 **	2240/45	452 (500-¾)	
*** CIRCLING	2460-1¾ 670 (700-1¾)	2460-2 670 (700-2)	2460-2½ 670 (700-2½)
WITHOUT LAST STEPDOWN FIX			
S-LOC 34 ****	2320/55	532 (600-1)	

DYESS AFB (KDYS)

Amdt 3 10NOV16

HI-ILS or LOC X RWY 34