

WAAS CH 82319 W31A	APP CRS 310°	Rwy Ldg TDZE 7901 3601 Apt Elev 3607
--	------------------------	--


RNAV (GPS) Y RWY 31
RICK HUSBAND AMARILLO INTL (AMA)

⚠ DME/DME RNP-0.3 NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -14°C (7°F) or above 46°C (116°F). When local altimeter setting not received, use Borger altimeter setting: increase DA to 4004 and all visibilities $\frac{5}{8}$ mile; increase all MDA 160 feet and visibility Cat C and D $\frac{1}{2}$ mile. Baro-VNAV and VDP NA when using Borger altimeter setting.


ASR

MISSED APPROACH: Climb to 6100 direct MOVEO and on track 317° to LANIT and hold.

ATIS 118.85 350.3	AMARILLO APP CON★ 119.5 307.0	AMARILLO TOWER★ 118.3 (CTAF) 257.9	GND CON 121.9 348.6	CLNC DEL 121.65 239.275	UNICOM 122.95
-----------------------------	---	---	-------------------------------	-----------------------------------	-------------------------



ELEV 3607	D	TDZE 3601
------------------	----------	------------------



6100

↑

MOVVOE

✦

tr 317°

△

LANIT

*LNAV only.

IMOBE

1.7 NM to RW31

RW31

0.9 NM to RW31

PAMPE

5400

CEVEX

5400

GP 3.04°

TCH 52

0.9

0.8

3.7 NM

6.6 NM

*4180

310°

CATEGORY	A		B	C	D
LPV DA			3851-¾	250 (300-¾)	
LNAV/VNAV DA			3851-¾	250 (300-¾)	
LNAV MDA			3940-1	339 (400-1)	
CIRCLING	4080-1	473 (500-1)	4240-1¾ 633 (700-1¾)	4280-2¼ 673 (700-2¼)	