



WAAS CH 45999 W16A	APP CRS 164°	Rwy Ldg TDZE 163 Apt Elev 171
--	------------------------	---

RNAV (GPS) Y RWY 16

BELLINGHAM INTL (BLI)

RNP APCH. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -10°C or above 54°C. #RVR 1800 authorized with use of FD or AP or HUD to DA.	MALSR 	MISSED APPROACH: Climb to 700 then climbing right turn to 2000 direct TECUV and hold.
--	--	--

ATIS 134.45	VICTORIA TERMINAL APP CON 132.7	BELLINGHAM TOWER ★ 124.9 (CTAF) 0 379.3	GND CON 127.4 379.3	UNICOM 122.95
-----------------------	---	---	-------------------------------	-------------------------



4 NM Holding Pattern		SECOP	WUGUT	TECUV
6000 2000		344° 164°	164° 2000	*1.1 NM to RWY 16 RWY 16
GP 3.00° TCH 51		6 NM	4.5 NM	1.1 NM
CATEGORY	A	B	C	D
LPV DA #	363/24 200 (200-½)			
LNAV/VNAV DA	491/30 328 (400-¾)			
LNAV MDA	560/24 397 (400-½)		560/35 397 (400-¾)	
CIRCLING	640-1 469 (500-1)		900-2 729 (800-2) 1160-3 989 (1000-3)	