

WAAS

CH **58218**

W14A

APP CRS

139°

Rwy Ldg

10000

TDZE

442

Apt Elev

459

RNAV (GPS) RWY 14L

SCOTT AFB/MIDAMERICA ST LOUIS (BLV)

RNAV 1 - GPS.

▼

▲

ASR

Rwy 14L helicopter visibility reduction below RVR 4000 NA.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C.

MISSED APPROACH: Climb to 2300 direct JIRUB and on track 103° to DUTMY and hold.

ATIS ★	ST LOUIS APP CON	SCOTT TOWER	GND CON	CLNC DEL
128.7 256.7	125.2 281.5	128.25 253.5	119.2 275.8	119.875 263.025

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).

2300

JIRUB

DUTMY

ELEV 459

D

TDZE 442

BALLY

OFAFY

DMJPS

RW14L

2100

2100

1620

1.2 NM to RW14L

GP 3.00°

TCH 55

6 NM

1.5 NM

2.3 NM

1.2 NM

CATEGORY	A	B	C	D
LPV DA	694/40 252 (300-¾)			
LNAV/VNAV DA	934-1⅜ 492 (500-1⅜)			
LNAV MDA	900/55 458 (500-1)	900-1⅜ 458 (500-1⅜)		
CIRCLING	1000-1 541 (600-1)	1120-1 661 (700-1)	1240-2¼ 781 (800-2¼)	1240-2½ 781 (800-2½)

REIL Rwy 14L

HIRL Rwys 14R-32L and 14L-32R

BELLEVILLE, ILLINOIS

Orig-B 08SEP22

SCOTT AFB/MIDAMERICA ST LOUIS (BLV)

38°33'N-89°50'W

RNAV (GPS) RWY 14L