

**PHOENIX DEP CON**  
124.9 353.8  
A11S  
133.5 270.275  
CINC DEL  
135.05  
GND CON  
128.25 275.8  
GATEWAY TOWER ★  
120.6 289.4

**TOP ALTITUDE:  
ASSIGNED BY ATC**

RNAV 1 - GPS.  
RADAR required.

NOTE: Turbojets and turboprops only.  
 NOTE: Aircraft requesting FL220 and below must file BLYTHE Transition.  
 NOTE: Turbojets landing LAX, file WLVRN Transition.  
 NOTE: Aircraft landing other than LAX and turboprops landing at LAX: Requesting FL240 and above, file HRRBR Transition.  
 NOTE: Aircraft departing KGEU and KGYR ATC assigned only.

**TAKEOFF MINIMUMS**  
 Rwy 12L/C/R: Standard with a minimum climb of 250'/NM to 3100.  
 Rwy 30L/C/R: Standard.

**DEPARTURE ROUTE DESCRIPTION**

TAKEOFF RUNWAYS 12L/C/R: Climb on heading 124° or as assigned by ATC, thence. . . .  
 TAKEOFF RUNWAYS 30L/C/R: Climb on heading 304° or as assigned by ATC, thence. . . .  
 . . . for RADAR vectors to KEENS, then on track 259° to IZZZO, then on (transition).  
 Maintain ATC assigned altitude, expect filed altitude 3 minutes after departure.

**BLYTHE TRANSITION (IZZZO8.BLH)**  
**HRRBR TRANSITION (IZZZO8.HRRBR)**  
**WLVRN TRANSITION (IZZZO8.WLVRN)**