


LOC/DME I-RGS 110.15 Chan 38 (Y)	APP CRS 183°	Rwy Idg 9000 TDZE 744 Apt Elev 748
--	------------------------	---


ILS or LOC RWY 18R
CHARLOTTE/DOUGLAS INTL (CLT)

RADAR required for procedure entry. DME or RADAR required.		ALSIF-2 	MISSED APPROACH: Climb to 1200 then climbing right turn to 4000 on CLT VOR/DME R-250 to STULL INT/CLT 13 DME and hold, continue climb-in-hold to 4000.
Simultaneous approach authorized. CILOV minimums: For inop ALS, increase S-LOC 18R all Cats visibility to RVR 4500.			

D-ATIS	CHARLOTTE APP CON	CHARLOTTE TOWER	GND CON	CLNC DEL
ARR 121.15 DEP 132.1	(001°-119°) 128.32 (120°-295°) 120.05 (296°-360°) 134.75 (180°-359°) 257.2 (360°-179°) 307.8	(Rwys 18L-36R) 118.1 257.8 (Rwy 18C-36C) 126.4 257.8 (Rwy 18R-36L) 133.35 257.8	121.8 348.6 (WEST) 121.9 348.6 (EAST)	127.15 348.6
				CPDLC



RUDKY I-RGS [20.8] RADAR		NELLA I-RGS [17.7] RADAR		WOVEN I-RGS [14.5] RADAR		EMERS I-RGS [11.4] RADAR		JHUNT I-RGS [8.2] RADAR		AUUDD I-RGS [6.3] RADAR		CILOV I-RGS [2.6]		*LOC only		STULL INT	
7000		6000		5000		4000		3000		2400		2400		*1200		IM	
183°		GS 3.00° TCH 55															
←3.2 NM→		3.2 NM		3.2 NM		3.2 NM		1.9 NM		3.7 NM		0.5		0.7		0.1	
CATEGORY		A				B				C				D			
S-ILS 18R		944/18 200 (200-½)															
S-LOC 18R		1200/24 456 (500-½)								1200/45 456 (500-¾)							
CILOV FIX MINIMUMS (DME REQUIRED)																	
S-LOC 18R		1040/24 296 (300-½)															



SE-2, 04 SEP 2025 to 02 OCT 2025

SE-2, 04 SEP 2025 to 02 OCT 2025