

WAAS CH 70307 W27A	APP CRS 265°	Rwy Idg TDZE Apt Elev	7985 6121 6160
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 27

CHEYENNE RGNL/JERRY OLSON FLD (CYS)


RNP APCH.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -24°C or above 45°C. For inop ALS, increase LNAV/VNAV all Cts visibility to RVR 4000.
RVR 1800 authorized with use of FD or AP or HUD to DA.



MISSED APPROACH: Climb to 6600, then climbing right turn to 10400 direct SENSE and hold, continue climb-in-hold to 10400.

ATIS 134.425 278.3	CHEYENNE APP CON★ 124.55 263.075	CHEYENNE TOWER★ 118.7(CTAF) 0 257.8	GND CON 121.9 254.275	UNICOM 122.95
------------------------------	--	---	---------------------------------	-------------------------



ELEV 6160	D	TDZE 6121
-----------	----------	-----------

6600

10400

SENSE

TWR 6256

9270 X 150

0.7% UP

0.4% DOWN

265° to RW27

6600

10400

SENSE

*LNAV only

*1.3 NM to RW27

RW27

265°

7800

266°

086°

7800

GP 3.00°

TCH 55

CATEGORY	A	B	C	D
LPV DA#	6321/24 200 (200-½)			
LNAV/VNAV DA	6376/24 255 (300-½)			
LNAV MDA	6560/24 439 (400-½)		6560/40 439 (400-¾)	
CIRCLING	6640-1 480 (500-1)		6900-2 740 (800-2) 6920-2½ 760 (800-2½)	

6 NM Holding Pattern

6600

10400

SENSE