

NDB DXB

385

APP CRS

354°

Rwy Idg

5494

TDZE

197

Apt Elev

202

NDB RWY 36

BEAUREGARD RGNL (DRI)

▼

NA

Inoperative table does not apply. Visibility reduction by helicopters NA. When local altimeter setting not received, use Fort Polk altimeter setting and increase all MDAs 60 feet and S-36 visibility Cat D 1/2 SM and Circling Cats C/D 1/4 SM.

ODALS

MISSED APPROACH: Climb to 1000 then climbing left turn to 1700 direct DXB NDB and hold.

AWOS-3PT	POLK APP CON	UNICOM
118.225	123.7 261.3	122.8 (CTAF) 0

ELEV 202

TDZE 197

REIL Rwy 18 0

MIRL Rwy 18-36 0

FAF to MAP 4.2 NM

Knots	60	90	120	150	180
Min:Sec	4:12	2:48	2:06	1:41	1:24

One Minute Holding Pattern				
1000	1700	DXB	DXB NDB	
VGSi and descent angles not coincident (VGSi Angle 3.00/TCH 50).				
CATEGORY	A	B	C	D
S-36	700-1	503 (500-1)	700-1½	503 (500-1½)
CIRCLING	720-1	518 (600-1)	780-1½	1000-2½
			578 (600-1½)	798 (800-2½)

DE RIDDER, LOUISIANA

Amtd 5B 04NOV21

30°50'N-93°20'W

BEAUREGARD RGNL (DRI)

NDB RWY 36

SC-4, 04 SEP 2025 to 02 OCT 2025

SC-4, 04 SEP 2025 to 02 OCT 2025