


WAAS CH 86812 W24A	APP CRS 245°	Rwy Ldg TDZE Apt Elev	7500 730 732
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 24
ERIE INTL/TOM RIDGE FLD (ERI)

RNP APCH - GPS.		MALSR	MISSED APPROACH: Climb to 3000 direct LADVE and hold.
⚠ Circling to Rwy 2 and 20 NA at night. Circling NA southeast of Rwy 6-24. ⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. For inop ALS increase LNAV/VNAV all Cats visibility to RVR 6000.			

ATIS 120.35	BUFFALO APP CON ★ 121.0 257.8	ERIE TOWER ★ 118.1 (CTAF) 0 257.8	GND CON 121.9	CLNC DEL 126.8	UNICOM 122.95
-----------------------	---	---	-------------------------	--------------------------	-------------------------



3000

↑

LADVE

YUYXI

2.6 NM to RW24

DEFJO

2400

JONLI

4 NM Holding Pattern

1.2 NM to RW24

1.2 NM

1.4 NM

2.5 NM

6.5 NM

1600

2400

065°

245°

GP 3.00°

TCH 55

6000

3200

CATEGORY	A	B	C	D
LPV DA	942/24		212 (300-½)	
LNAV/VNAV DA	1146/40		416 (500-¾)	
LNAV MDA	1160/24 430 (500-½)		1160/40 430 (500-¾)	
CIRCLING	1160-1 428 (500-1)	1200-1 468 (500-1)	1200-1½ 468 (500-1½)	1340-2 608 (700-2)

