



WAAS CH 82417 W32A	APP CRS 321°	Rwy Ldg TDZE Apt Elev	8001 800 815
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 32

FORT WAYNE INTL (FWA)

ASR	For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). DME/DME RNP-0.3 NA. ** RVR 1800 authorized with use of FD or AP or HUD to DA.		MALSR	MISSED APPROACH: Climb to 3000 direct LABIC and hold.	
ATIS	FORT WAYNE APP CON	FORT WAYNE TOWER	GND CON	CLNC DEL	
121.25 360.825	127.2 284.6	119.1 269.325	121.9 348.6	124.75	



3000

LABIC

↑

★

* LNAV only

* 1.3 NM to RW32

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 76).

DABYA

2300

CABAC

2300

4 NM Holding Pattern

141° →

← 321°

3000

GP 3.00°

TCH 56

1.3

3.2 NM

6 NM

CATEGORY	A	B	C	D
LPV DA	**1000/24 200 (200-½)			
LNAV/VNAV DA	1250/50 450 (500-1)			
LNAV MDA	1280/24	480 (500-½)	1280/50	480 (500-1)
CIRCLING	1300-1	485 (500-1)	1420-1¾ 605 (700-1¾)	1520-2¼ 705 (800-2¼)