

KINGDOM FIVE DEPARTURE

TOP ALTITUDE: ASSIGNED BY ATC

RADAR and DME required.

LONE STAR DEP CON	
118.1 306.95 (NORTH)	
35.975 379.9 (SOUTH)	
ATIS	
120.7	
CLINC DEL	
124.65	
GND CON	
121.9	
MEACHAM TOWER	
118.3 257.8	

TAKEOFF MINIMUMS

Rwys 16, 17: Standard.

Rwy 34: 300-17% or standard with minimum climb of 225'/NM to 1100, or alternatively, with standard takeoff minimums and a normal 200'/NM climb gradient; takeoff must occur no later than 2000' prior to DER.

Rwy 35: 300-1¼ or standard with minimum climb of 210'/NM to 900, or alternatively, with standard takeoff minimums and a normal 200'/NM climb gradient¹, takeoff must occur no later than 1300' prior to DER.

NOTE: LUBBOCK Transition: For all aircraft overflying the MQP VORTAC westbound or direct.

NOTE: MILSAP Transition: For all aircraft overflying the MQP VORTAC westbound or direct.

NOTE: PODDE Transition: ATC assigned.

NOTE: WICHITA FALLS Transition: For all aircraft landing within the Wichita Falls terminal area or overflying the SPS VORTAC.

NOTE: For all aircraft requesting 17000 and below.

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

SC-2, 04 SEP 2025 to 02 OCT 2025