

WAAS CH 77706 W23B	APP CRS 230°	Rwy Ldg 11200 TDZE 783 Apt Elev 796
--	------------------------	--

RNAV (GPS) Y RWY 23R

INDIANAPOLIS INTL (IND)

⚠

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inoperative ALS, increase LNAV Cat C/D visibility to RVR 6000. Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.
** RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSRL

⬆

⬆

⬆

MISSED APPROACH:

Climb to 1500 then climbing right turn to 3000 direct KEADY and hold.

D-ATIS 134.25	INDIANAPOLIS APP CON 128.175 317.8	INDY TOWER 120.9 251.1	GND CON 121.9	CLNC DEL 128.75 251.1	CPDLC
-------------------------	--	----------------------------------	-------------------------	---------------------------------	-------

Procedure NA for arrivals at CLANG on V14-192-210 northeast bound.

ELEV 796	D	TDZE 783	
1500 3000 KEADY VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).			
*LNAV only			
RW23R 1.1 NM 4.4 NM 4.4 NM 3.1 NM			
CATEGORY	A	B C D	
LPV DA	**983/24 200 (200-½)		
LNAV/VNAV DA	1165/40 382 (400-¾)		
LNAV MDA	1200/24 417 (500-½)	1200/40 417 (500-¾)	
CIRCLING	1420-1 624 (700-1)	1420-1¾ 624 (700-1¾) 1560-2½ 764 (800-2½)	

INDIANAPOLIS, INDIANA

Amtd 4A 17AUG17

39°43'N-86°18'W

INDIANAPOLIS INTL (IND)

RNAV (GPS) Y RWY 23R