

LINCOLN, NEBRASKA

HI-VOR/DME or TACAN RWY 36

VORTAC LNK 116.1 Chan 108	APCH CRS 360°	Rwy Idg 12,901 TDZE 1175 Arpt Elev 1219
---	-------------------------	--

[USAF]

LINCOLN (KLNK)

RADAR required

T * When ALS inop, increase CAT E vis to 1 $\frac{3}{8}$ miles.
 ** When ALS inop, increase CAT CDE vis to 1 $\frac{5}{8}$ miles.


MALSR

MISSED APPROACH: Climb to 3000 direct LNK VORTAC then via LNK R-360 to BUMBE 12 DME and hold.


ATIS 118.05 290.9	OMAHA APP CON 124.0 270.3	TOWER ★ 118.5 253.5	GND CON 121.9 275.8	CLNC DEL 120.7 225.4
----------------------	------------------------------	------------------------	------------------------	-------------------------

Inoperative table does not apply. • 1706

When local altimeter setting not received use
Beatrice altimeter setting.



EMERG SAFE ALT 100 NM 4800



CATEGORY	C	D	E
S-36 *	1620-7/8	445	(500-7/8)
CIRCLING	1760-1 1/2 541 (600-1 1/2)	1820-2 601 (700-2)	2040-3 821 (900-3)
BEATRICE ALTIMETER SETTING			
S-36 **	1720-1 1/8	545	(600-1 1/8)
CIRCLING	1860-1 3/4 641 (700-1 3/4)	1920-2 1/4 701 (800-2 1/4)	2140-3 921 (1000-3)

LINCOLN, NEBRASKA

40° 51'N-96° 46'W

LINCOLN (KLNK)

Amdt 5 31OCT24

HI-VOR/DME or TACAN RWY 36