

LOC/DME	I-LNR	Rwy Idg	5000
108.35	APP CRS	TDZE	717
Chan 20(Y)	270°	Apt Elev	717

LOC RWY 27

TRI-COUNTY RGNL (LNR)

DME required. RADAR required for procedure entry.

▼


NA

-30°C

Circling Rwy 18, 36 NA at night. Rwy 27 helicopter visibility reduction below ¾ SM NA. If local altimeter setting not received, use Dane County Rgnl-Truax Fld altimeter setting and increase all MDA 120 feet. Increase S-27 visibility Cat A/B ¼ SM, Cat C ½ SM, Circling visibility Cat B ¼ SM, Cat C ½ SM. Increase BOCAV fix minimums S-27 visibility Cat C ¼ SM, Circling Cat A/B ¼ SM, Cat C ½ SM.

MISSED APPROACH:
Climb to 2200 then climbing right turn to 3300 on heading 070° and on DLL R-224 to LENRE/DLL VORTAC 18 DME and hold.

ASOS 119.425	MADISON APP CON ★ 135.45 343.7	UNICOM 123.0 (CTAF) 0
-----------------	-----------------------------------	--------------------------



ELEV 717

TDZE 717

2200

3300

hdg 070°

DLL R-224

LENRE DLL 18

VGSI and descent angles not coincident (VGSI Angle 4.00/TCH 35).

PUDEE INT I-LNR 7

Remain within 10 NM

090°

2700

2700

2700

BOCAV I-LNR 3.5

I-LNR 2.4

I-LNR 1

3.05°

TCH 33

1580*

1.4 NM

1.1 NM

3.5 NM

*1680 when using Dane County Rgnl-Truax Fld altimeter setting.

CATEGORY	A	B	C	D
S-LOC 27	1580-1 863 (900-1)	1580-1¼ 863 (900-1¼)	1580-2½ 863 (900-2½)	NA
CIRCLING	1580-1¼	863 (900-1¼)	1580-2½ 863 (900-2½)	NA
BOCAV FIX MINIMUMS				
S-LOC 27	1360-1	643 (700-1)	1360-1¼ 643 (700-1¼)	NA
CIRCLING	1520-1	803 (900-1)	1560-2½ 843 (900-2½)	NA

REIL Rwy 9 and 27 0

MIRL Rwys 9-27 and 18-36 0

FAF to MAP 6 NM

Knots	60	90	120	150	180
Min:Sec	6:00	4:00	3:00	2:24	2:00