

WAAS
CH **60901**
W09B

APP CRS
094°

Rwy Ldg **10181**
TDZE **32**
Apt Elev **33**

RNAV (GPS) RWY 9R

MELBOURNE ORLANDO INTL (MLB)

RNP APCH - GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 2°C or above 54°C.

MALSR

MISSED APPROACH: Climb to 2000 direct ZUVOM and hold.

ATIS 132.55	ORLANDO APP CON 126.025 281.425	MELBOURNE TOWER ★ 118.2 (CTAF) 0 257.8	GND CON 121.9	CLNC DEL 121.9	CLNC DEL 126.025 (When twr closed)	UNICOM 122.95
-----------------------	---	---	-------------------------	--------------------------	---	-------------------------

Procedure NA for arrivals at PRESK on V159-537 northwest bound.

4 NM Holding Pattern

GP 3.00° TCH 55

6000 2000

274° 094°

SUROY

JINBA

1600

1.1 NM to RWY09R

RWY09R

WIXED

2000

ZUVOM

094°

6000 X 150

10181 X 150

TWR

REIL Rwy 27L

HIRL Rwy 9R-27L

MIRL Rws 5-23 and 9L-27R

TDZ/CL Rwy 9R

4 NM Holding Pattern		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 83).		2000		ZUVOM			
SUROY		JINBA		1600		1.1 NM to RWY09R			
6000 2000		1600		1600		RWY09R			
GP 3.00° TCH 55		6 NM		3.6 NM		1.1 NM			
CATEGORY	A	B	C	D					
LPV DA	232/18			200 (200-½)					
LNAV/VNAV DA	427/35			395 (400-⅝)					
LNAV MDA	480/24	448 (500-½)	480/45	448 (500-⅞)					
CIRCLING	500-1 467 (500-1)	560-1 527 (600-1)	680-1¾ 647 (700-1¾)	880-2¾ 847 (900-2¾)					

MELBOURNE, FLORIDA

Amtd 2 20FEB25

28°06'N-80°39'W

MELBOURNE ORLANDO INTL (MLB)

RNAV (GPS) RWY 9R