

MIAMI, FLORIDA

AL-257 (FAA)

24137


WAAS CH 86903 W26A	APP CRS 272°	Rwy Idg 8600 TDZE 9 Apt Elev 9
--	------------------------	---

RNAV (GPS) RWY 26R


MIAMI INTL (MIA)

RNP APCH - GPS.	MISSED APPROACH: Climb to 800 then climbing right turn to 4000 direct BRBRA and hold, continue climb-in-hold to 4000.
Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 9°C or above 54°C.	

D-ATIS ARR 119.15 DEP 133.675	MIAMI APP CON 124.85 322.3	MIAMI TOWER 118.3 256.9	GND CON 121.8 (Rwys 8L/R, 12, 26L/R) 127.5 (Rwys 9, 27, 30)	348.6	CUNC DEL 135.35	CPDLC
---	--------------------------------------	-----------------------------------	---	--------------	---------------------------	-------



ELEV 9	D	TDZE 9
--------	----------	--------



TDZ/CL Rwy 8R
REIL Rwys 8L and 26R
HIRL all Rwys

MIAMI, FLORIDA
Amdt 5 14JUL22

25°48'N-80°17'W

RNAV (GPS) RWY 26R

SE-3, 04 SEP 2025 to 02 OCT 2025