

LOC/DME I-BLY 110.3 Chan 40	APP CRS 191°	Rwy 19R Ldg 9205 TDZE 672 Apt Elev 728	Rwy 19L Ldg 4182 TDZE 674 Apt Elev 728
---	------------------------	---	---

ILS or LOC RWY 19R

GENERAL MITCHELL INTL (MKE)

RADAR required for procedure entry, RADAR or DME required for LOC only.

▼


For inop ALS, increase S-LOC 19R Cats C and D visibility to 1½ SM.
*RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR
Rwy 19R




MISSED APPROACH: Climb to 2800 then right turn direct BAE VOR/DME and hold.


D-ATIS 126.4	MILWAUKEE APP CON 126.5 307.0	MILWAUKEE TOWER 124.575 269.05	GND CON 121.8 263.125	CLNC DEL 120.8	CPDLC
------------------------	---	--	---------------------------------	--------------------------	-------



ELEV 728	TDZE 19R 672
TDZ/CL Rwy 1L	TDZE 19L 674
REIL Rwy 1R, 7L, 13, 25L, 25R, and 31	



HIRL Rwys 1L-19R and 7R-25L					
MIRL Rwys 1R-19L, 13-31, and 7L-25R					
FAF to MAP 6.5 NM					
Knots	60	90	120	150	180
Min:Sec	6:30	4:20	3:15	2:36	2:10

2800	BAE	VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 75).		ADELE
				
				
CATEGORY	A	B	C	D
S-ILS 19R*	872/24 200 (200-½)			
S-LOC 19R	1160/24	488 (500-½)	1160/50	488 (500-1)
SIDESTEP 19L	1160-1	486 (500-1)	1160-1½ 486 (500-½)	1160-2 486 (500-2)
C CIRCLING	1240-1	512 (600-1)	1240-1½ 512 (600-½)	1360-2 632 (700-2)

EC-3, 04 SEP 2025 to 02 OCT 2025

EC-3, 04 SEP 2025 to 02 OCT 2025