

LOC I-MSL	APP CRS	Rwy Idg	6694
109.7	297°	TDZE	551
		Apt Elev	551

ILS Z or LOC Z RWY 30

NORTHWEST ALABAMA RGNL (MSL)

DME required. RADAR required.

▼



▲

DME from MSL DME.
Simultaneous reception of I-MSL and MSL DME required.
For inop ALS increase S-LOC 30 Cats C/D visibility to 1 SM.

MALSR

MISSED APPROACH: Climb to 1200 then climbing right turn to 3000 on heading 020° to intercept RQZ VORTAC R-268 to JOBUM/RQZ VORTAC 42.5 DME/RADAR and hold, continue climb-in-hold to 3000.

ASOS	MEMPHIS CENTER	GCO	UNICOM
119.425	120.8 307.0	121.725	123.05 (CTAF) 0



ELEV 551	TDZE 551	1200	3000	RQZ R-268	JOBUM RQZ 42.5 RADAR	MSL DME	HUPOK MSL 7 RADAR	One Minute Holding Pattern
		1 NM		1.5 NM		2.8 NM		7.3 NM
CATEGORY	A		B		C		D	
S-ILS 30	751-1/2		200 (200-1/2)					
S-LOC 30	920-1/2 369 (400-1/2)		920-5/8 369 (400-5/8)					
CIRCLING	1040-1 489 (500-1)		1280-2 729 (800-2)		1280-2 729 (800-2 1/4)			