


WAAS CH 97322 W27A	APP CRS 268°	Rwy Idg TDZE 10 Apt Elev 36
--	------------------------	---

RNAV (GPS) RWY 27L

PHILADELPHIA INTL (PHL)

RNP APCH - GPS.	MALSR 	MISSED APPROACH: Climb to 500 then climbing left turn to 3000 direct WUDRR and hold.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 6000. * RVR 1800 authorized with use of FD or AP or HUD to DA.		

D-ATIS ARR 133.4 DEP 135.925	PHILADELPHIA APP CON 124.35 319.15	PHILADELPHIA TOWER 118.5 327.05 (Rwys 9L/27R, 8/26 and 17/35) 135.1 327.05 (Rwy 9R/27L)	GND CON 121.9 348.6	CLNC DEL 118.85 348.6
--	--	---	-------------------------------	---------------------------------



ELEV 36		D TDZE 10	
VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 73).			
CATEGORY	A	B	C
LPV DA*	210/24 200 (200-1/2)		
LNAV/DA VNAV	422/40 412 (400-3/4)		
LNAV MDA	540/24 530 (600-1/2)	540/55 530 (600-1)	
CIRCLING	540-1 504 (600-1)	600-1 564 (600-1)	620-1 1/2 584 (600-1 1/2) 720-2 1/4 684 (700-2 1/4)